Distribution Frame Accessories



2357-1 Vertical Mounting Bracket


Mounting Bars


Connector mounting bars are required on conventional and universal-type distributing frames to support central office connectors on the vertical side. They are zinc plated and dichromate dipped to assure a low resistance connection to ground the connector assembly.

Mounting Arrangements

The connector mounting hole arrangement on the mounting bar has drilled and tapped holes to mount the R399 connector. The frame mounting side has a universal mounting slot to fit various distribution frames.

Diagrams





Mounting Bar Connector Capacity

Connector	— Frame	Height —
Туре	7'	8'
R399, stub up	700 pair	900 pair
R399, stub down	800 pair	1000 pair

Mounting Bars - R366, R399, AR399 and R399C

Catalog Number	Maximum Capacity	Overall Length	Mounting Arrangement	Minimum Frame Height
P48271	100 pair	8.4 "	Wall mount	_
P44036	800 pair	67.66"	Universal	7'
P44037	900 pair	76.12"	Universal	8'

Accessories

Catalog Number	Part Number	Description
23571	F150645	Terminal block mounting brackets for vertical mounting

<u>EmersonNetworkPower.com/EnergySystems</u> (North America) <u>EmersonNetworkPower.eu/EnergySystems</u> (EMEA)

© Emerson Network Power, Energy Systems, North America, Inc. 2014.

Business-Critical Continuity™, Emerson Network Power™, the Emerson Network Power logo, Emerson™ and Consider it Solved are service marks and trademarks of Emerson Electric Co. EnergyMaster™, eSure™, NetPerform™, NetReach™, NetSpan™, NetSure™ and NetXtend™ are trademarks of Emerson Network Power, Energy Systems, North America, Inc. Any other product, brand, or company names or logos are the property of the respective owner.

